

# REINFORCED HOISING (PTY) LTD

## HOSE SPECIFICATIONS

### CRF

#### REH Clear Reinforced Fuel Hose

**Material:** Liner: X40 PR TQ3  
Cover: X4000U1 Clear V/PVC,

Specification Requirement RCRT20						
	3	5	6,3	6,3	8	10
Inner Liner max. inside diameter.	3,0	5,0	6,4	6,4	8,2	10,2
Inner Liner min. inside diameter.	2,9	4,9	6,2	6,2	7,9	9,8
Inner Liner max. wall thickness.	1,0	1,2	1,5	1,5	1,5	1,6
Inner Liner min. wall thickness.	0,8	1,0	1,3	1,3	1,3	1,4
Number of yarn plies – 1000 Den.	1	1	1	1	1	2
Number of bobbins.	12	12	16	16	16	16
Max. Outer Cover thickness.	0,9	1,0	1,2	1,2	1,25	1,3
Min. Outer Cover thickness.	0,8	0,8	1,0	1,0	1,0	1,1
Weight per meter in Gms.	60	75	95	95	115	135
Weight per 30m roll in Kgs.	1,80	2,25	2,85	2,85	3,45	4,05
Min. Burst pressure in Kpa.	70	66	59	59	52	45

These Specifications are the Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: March 1, 2013

Issue No: 1

Issuing Officer: T. Niemand

Signature \_\_\_\_\_

*Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.*