

REINFORCED HOSING (PTY) LTD

HOSE SPECIFICATIONS

RCRT20

REH Clear Reinforced Tubing

Material: X4000 Clear V/PVC

Specification Requirement RCRT20										
	3	5	6,3	8	10	12	16	20	25	32
Inner Liner max. inside diameter.	3,0	5,0	6,4	8,2	10,2	12,8	16,2	20,2	25,5	32,0
Inner Liner min. inside diameter.	2,9	4,9	6,2	7,9	9,8	12,0	15,8	19,0	24,0	31,0
Inner Liner max. wall thickness.	1,0	1,2	1,5	1,5	1,6	1,8	2,0	2,1	2,3	3,0
Inner Liner min. wall thickness.	0,8	1,0	1,3	1,3	1,4	1,6	1,8	1,9	2,1	2,75
Number of yarn plies – 1000 Den.	1	1	1	1	2	2	2	2	3	3
Number of bobbins.	12	12	16	16	16	16	16	24	24	32
Max. Outer Cover thickness.	0,9	1,0	1,2	1,25	1,3	1,5	1,5	1,8	1,9	2,3
Min. Outer Cover thickness.	0,8	0,8	1,0	1,0	1,1	1,3	1,3	1,6	1,7	2,0
Weight per meter in Gms.	48	71	100	110	130	190	240	305	500	729
Weight per 30m roll in Kgs.	1,44	2,13	3,0	3,3	3,9	5,7	7,2	9,2	15,0	21,8
Min. Burst pressure in Kpa.	60	60	60	52	45	42	40	40	40	40

These Specifications are the Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: March 1, 2017

Issue No: 3

Issuing Officer: T. Niemand

Signature _____

Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.