

REINFORCED HOSING (PTY) LTD

HOSE SPECIFICATIONS

REH 500

5 Year - Standard Duty Agricultural Dragline Hose

Liner Material: I3050HMF V/PVC, I2050B7 V/PVC, RH40 PVC
Cover Material: I3050HMF V/PVC, I2050B7 V/PVC, M356064 GREEN V/PVC, RH40 PVC

Specification Requirement REH 10 YEAR	Hose size in millimetres	
	12mm	20mm
Inner Liner max. inside diameter.	12,3	20,0
Inner Liner min. inside diameter.	11,7	18,6
Inner Liner max. wall thickness.	1,8	1,8
Inner Liner min. wall thickness.	1,6	1,6
Number of yarn plies – 1100 Den.	1	2
Number of bobbins.	16	24
Max. Outer Cover thickness.	1,30	1,40
Min. Outer Cover thickness.	1,10	1,20
Weight per meter in Gms.	190	300
Weight per 30m roll in Kgs.	5,7	9,00
Min. Burst pressure in Kpa.	4000	3500

These Specifications are the Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: March 1, 2013

Issue No: 2

Issuing Officer: T. Niemand

Signature _____

Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.