

REINFORCED HOISING (PTY) LTD

HOSE SPECIFICATIONS

SHM – Suction Hose – Medium Yellow

Material: X4000 V/PVC and RX303/Y5 V/PVC

Code	ID		OD	Thickness	Length	Working	Vacuum	Bend	Mass
	mm	Inch	mm	mm	m	Pressure	Rating	Radius	per metre
SHM25030	25	2	31	3mm	30	600kpa	750	60	0.40
SHM32030	32	1¼	38	3mm	30	600kpa	750	70	0.50
SHM40030	40	1½	46	3mm	30	500kpa	750	90	0.70
SHM50030	50	2	58	4mm	30	500kpa	750	130	0.93
SHM63030	63	2½	71	4mm	30	500kpa	750	180	1.20
SHM75030	75	3	83	4mm	30	400kpa	750	200	1.60
SHM10030	100	4	110	5mm	30	400kpa	750	300	2.50
SHM12530	125	5	137	6mm	30	350kpa	750	500	4.00
SHM15030	150	6	166	8mm	30	300kpa	750	700	6.00

These Specifications are used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: September 1, 2019

Issue No: 1

Issuing Officer: T. Niemand

Signature _____

Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.